

IN THE CLAIMS:

Please amend claims as follows:

1. (Currently Amended) A liquid fuel filter for removing sulfur-containing compounds from a liquid fuel, comprising:

a hollow housing body defining a chamber therein;

an inlet connected to the housing body and in fluid communication with the chamber thereof;

an outlet connected to the housing body and in fluid communication with the chamber thereof;

a liquid fuel filter media disposed in the housing chamber for filtering liquid fuel and for removing sulfur compounds therefrom; the liquid fuel filter media comprising:

a plurality of fibers; and

a sulfur-treating composition operatively associated with the fibers for reacting with sulfur-containing compounds.

2. (Currently Amended) The ~~fuel filter~~liquid fuel filter of claim 1, wherein the sulfur-treating composition is selected for its ability to react with thiophenes.

3. (Currently Amended) The ~~fuel filter~~liquid fuel filter of claim 1, wherein said ~~filter media~~liquid fuel filter media fibers comprise a plurality of shaped fibers having hollow channels formed therein.

4. (Currently Amended) The ~~fuel filter~~liquid fuel filter of claim 3, wherein said sulfur-treating composition ~~comprises~~comprises a sorbent material disposed within the hollow channels of the fibers.

5. (Currently Amended) The ~~fuel filter~~liquid fuel filter of claim 4, wherein said sorbent material is selected from the group consisting of activated carbon, zeolites, clay, silica gel, silicon dioxide, aluminum oxide and mixtures thereof.

6. (Currently Amended) The ~~fuel filter~~liquid fuel filter of claim 1, wherein the sulfur-treating composition comprises an electron acceptor, and wherein the sulfur-treating composition is adapted to form a coordination complex with a sulfur-containing compound.

7. (Currently Amended) The ~~fuel filter~~liquid fuel filter of claim 1, wherein the sulfur-treating composition comprises a reagent selected from the group consisting of metals, metal oxides, metallic salts, organometallic compounds, catalysts, and oxidizing agents.

8. (Currently Amended) The ~~fuel filter~~liquid fuel filter of claim 4, wherein the sulfur-treating composition further comprises a reagent selected from the group consisting of metals, metal oxides, metallic salts, organometallic compounds, catalysts, and oxidizing agents.

9. (Currently Amended) The ~~fuel filter~~liquid fuel filter of claim 1, wherein the sulfur-treating composition comprises a liquid emulsion.

10. (Currently Amended) A ~~fuel filter~~liquid fuel filter for removing sulfur-containing compounds from a liquid fuel, comprising:

 a thin-walled hollow housing body defining a chamber therein;

 an inlet connected to the housing body and in fluid communication with the chamber thereof;

 an outlet connected to the housing body and in fluid communication with the chamber thereof;

a ~~filter media~~liquid fuel filter media disposed in the housing chamber for filtering liquid fuel and for removing sulfur-containing compounds therefrom; the ~~filter media~~liquid fuel filter media comprising:

- a plurality of substrate particles; and
- a reagent operatively associated with a plurality of particles selected from said substrate particles, said reagent being capable of reacting with thiophenes.

11. (Currently Amended) The liquid fuel filter of claim 10, wherein said substrate particles comprise a substance selected from the group consisting of activated carbon, zeolites, clay, silica gel, silicon dioxide, aluminum oxide and mixtures thereof.

12. (Currently Amended) The liquid fuel filter of claim 10, wherein said reagent is selected from the group consisting of metals, metal oxides, metallic salts, organometallic compounds, catalysts, and oxidizing agents.

13. (withdrawn) A system for reducing a concentration of sulfur-containing compounds in a liquid fuel, comprising: a metering pump for adding a precipitating agent to said fuel at a first location; and a filter for removing a precipitate from said fuel downstream of said metering pump, said filter comprising: a thin-walled hollow housing body defining a chamber therein; an inlet connected to the housing body and in fluid communication with the chamber thereof; an outlet connected to the housing body and in fluid communication with the chamber thereof; and a ~~filter media~~liquid fuel filter media disposed in the housing chamber for filtering precipitate from said liquid fuel and for thereby removing sulfur-containing compounds therefrom.

14. (withdrawn) A method of filtering fuel, comprising the steps of:

- a) transferring the fuel from a reservoir through a fuel line and to a ~~fuel filter~~liquid fuel filter;

b) treating the fuel by passing it through the ~~fuel filter~~liquid fuel filter and over a ~~filter media~~liquid fuel filter media housed therein, said ~~filter media~~liquid fuel filter media comprising a reactant selected for its ability to react with thiophenes and reduce the concentration thereof in said fuel; whereby the concentration of sulfur-containing compounds in the fuel is reduced.

15. (withdrawn) The method of claim 14, wherein the ~~filter media~~liquid fuel filter media comprises a plurality of shaped fibers having hollow channels formed therein.

16. (withdrawn) The method of claim 15, wherein a plurality of solid particles are disposed within the hollow channels of the fibers.

17. (withdrawn) The method of claim 14, wherein said ~~filter media~~liquid fuel filter media comprises a plurality of substrate particles comprising a substance selected from the group consisting of activated carbon, zeolites, clay, silica gel, silicon dioxide, aluminum oxide and mixtures thereof.

18. (withdrawn) The method of claim 17, wherein said substrate particles are operatively associated with a substance selected from the group consisting of metals, metal oxides, metallic salts, organometallic compounds, catalysts, and oxidizing agents.

19. (withdrawn) The method of claim 18, wherein said ~~filter media~~liquid fuel filter media further comprises a reagent selected from the group consisting of metals, metal oxides, metallic salts, organometallic compounds, catalysts, and oxidizing agents.

20. (withdrawn) A method of reducing a concentration of sulfur-containing compounds from a liquid fuel, comprising:

adding a precipitating agent to said fuel at a first location between a fuel storage tank and a fuel application, whereby a sulfur-containing compound in said fuel is

precipitated out of solution therein; and passing said fuel through a ~~fuel filter~~liquid fuel filter to remove said precipitate from said fuel.

21. (withdrawn) A method of filtering fuel of a reservoir in fluid communication with a ~~fuel filter~~liquid fuel filter, comprising:

transferring fuel from the reservoir to the ~~fuel filter~~liquid fuel filter;

passing fuel through a ~~filter media~~liquid fuel filter media disposed within the ~~fuel filter~~liquid fuel filter, said ~~filter media~~liquid fuel filter media comprising: a sulfur-treating composition operatively associated with said ~~filter media~~liquid fuel filter media and for reacting with sulfur-containing compounds, wherein the concentration of sulfur-containing compounds in the fuel is reduced by passing the fuel through said ~~filter media~~liquid fuel filter media.

22. (withdrawn) The method of claim 21, wherein the ~~filter media~~liquid fuel filter media comprises a plurality of shaped fibers having hollow channels formed therein.

23. (withdrawn) The method of claim 22, wherein a plurality of solid particles are disposed within the hollow channels of the fibers.

24. (withdrawn) The method of claim 21, wherein said ~~filter media~~liquid fuel filter media comprises a plurality of substrate particles comprising a substance selected from the group consisting of activated carbon, zeolites, clay, silica gel, silicon dioxide, aluminum oxide and mixtures thereof.

25. (withdrawn) The method of claim 24, wherein said substrate particles are operatively associated with a substance selected from the group consisting of metals, metal oxides, metallic salts, organometallic compounds, catalysts, and oxidizing agents.

26. (withdrawn) The method of claim 25, wherein said ~~filter media~~liquid fuel filter media further comprises a reagent selected from the group consisting of metals, metal oxides, metallic salts, organometallic compounds, catalysts, and oxidizing agents.

27. (New) A fuel filter for removing sulfur-containing compounds from a liquid fuel, comprising:

a hollow housing body defining a chamber therein;

an inlet connected to the housing body and in fluid communication with the chamber thereof;

an outlet connected to the housing body and in fluid communication with the chamber thereof;

a fuel filter media disposed in the housing chamber for filtering liquid fuel and for removing sulfur compounds therefrom; the fuel filter media comprising:

a plurality of shaped fibers having hollow channels formed therein;

and

a sulfur-treating composition operatively associated with the fibers.

28. (New) A fuel filter for removing sulfur-containing compounds from a liquid fuel, comprising:

a hollow housing body defining a chamber therein;

an inlet connected to the housing body and in fluid communication with the chamber thereof;

an outlet connected to the housing body and in fluid communication with the chamber thereof;

a fuel filter media disposed in the housing chamber for filtering liquid fuel and for removing sulfur compounds therefrom; the fuel filter media comprising:

a plurality of fibers; and

a sulfur-treating composition operatively associated with the fibers,
wherein the sulfur-treating composition comprising an electron acceptor,.

29. (New) A fuel filter for removing sulfur-containing compounds from a liquid fuel,
comprising:

a hollow housing body defining a chamber therein;

an inlet connected to the housing body and in fluid communication with
the chamber thereof;

an outlet connected to the housing body and in fluid communication with
the chamber thereof;

a fuel filter media disposed in the housing chamber for filtering liquid fuel
and for removing sulfur compounds therefrom; the fuel filter media comprising:

a plurality of fibers; and

a sulfur-treating composition comprising a liquid emulsion
operatively associated with the fibers.